


WHY DO WE EVEN NEED OAUTH ANYWAY?

AARON PARECKI

@AARONPK



Thank You to Our Sponsors and Hosts!



OWASP
**NEW
ZEALAND**
owasp.org.nz



QUANTUM
SECURITY



CyberCX

DATACOM



snyk



Auth0

Checkmarx



HCL AppScan


kordia



**LATERAL
SECURITY**




**MICRO
FOCUS**



Pulse Security
www.pulsesecurity.co.nz



RedShield



Flux

SEQA
Information Security



Cobalt



LACEWORK




Secure**Flag**




Without them, OWASP New Zealand Day couldn't happen











I E T F®

[[Search](#)] [[txt](#)] [[html](#)] [[pdf](#)] [[Tracker](#)] [[WG](#)] [[Email](#)] [[Diff1](#)] [[Diff2](#)] [[Nits](#)]

Versions: ([draft-parecki-oauth-v2-1](#)) [00](#) [01](#) [02](#) [03](#)
[04](#)

OAuth Working Group
Internet-Draft
Intended status: Standards Track
Expires: 8 April 2022

D. Hardt
Hellö
A. Parecki
Okta
T. Lodderstedt
yes.com
5 October 2021

okta

The OAuth 2.1 Authorization Framework
draft-ietf-oauth-v2-1-04

Abstract

The OAuth 2.1 authorization framework enables a third-party application to obtain limited access to an HTTP service, either on behalf of a resource owner by orchestrating an approval interaction between the resource owner and an authorization service, or by allowing the third-party application to obtain access on its own behalf. This specification replaces and obsoletes the OAuth 2.0 Authorization Framework described in [RFC 6749](#).

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

The OAuth 2.0 Authorization Framework

Abstract

The OAuth 2.0 authorization framework enables a third-party application to obtain limited access to an HTTP service, either on behalf of a resource owner by orchestrating an approval interaction between the resource owner and the HTTP service, or by allowing the third-party application to obtain access on its own behalf. This specification replaces and obsoletes the OAuth 1.0 protocol described in [RFC 5849](#).

Status of This Memo

This is an Internet Standards Track document.

This document is a product of the Internet Engineering Task Force (IETF). It represents the consensus of the IETF community. It has received public review and has been approved for publication by the Internet Engineering Steering Group (IESG). Further information on Internet Standards is available in [Section 2 of RFC 7741](#).

Information about the current status of this document, any errata, and how to provide feedback on it may be obtained at <http://www.rfc-editor.org/info/rfc6749>.

Copyright Notice

Copyright (c) 2012 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1. Introduction

1.1. Roles

1.2. Protocol Flow

1.3. Authorization Grant

1.3.1. Authorization Code

1.3.2. Implicit

1.3.3. Resource Owner Password Credentials

1.3.4. Client Credentials

1.4. Access Token

1.5. Refresh Token

1.6. TLS Version

1.7. HTTP Redirections

4

6

7

8

8

8

9

9


10


10

12

12

BUILDING YOUR APPLICATION





Secure

| <https://yelp.com/>

f Sign in with Facebook

g⁺ Sign in with Google

in Sign in with LinkedIn

Sign in with Twitter

A cartoon illustration of a young man with dark hair and glasses, looking surprised or questioning. He is pointing his right index finger towards a sign in the upper right corner of the image. The sign contains four social media login buttons. The background shows a window with a grid pattern.

f Sign in with Facebook

g+ Sign in with Google

in Sign in with LinkedIn

t Sign in with Twitter

IS THIS OAUTH?

**LIMIT/DELEGATE
ACCESS TO DATA**

Are your friends already on Yelp?

Many of your friends may already be here, now you can find out. Just log in and we'll display all your contacts, and you can select which ones to invite! And don't worry, we don't keep your email password or your friends' addresses. We loathe spam, too.

Your Email Service

☐  Hotmail ☐  MAIL ☐  Mail ☒ 

Your Email Address

(e.g. bob@gmail.com)

Your Gmail Password

(The password you use to log into your Gmail email)

[Skip this step](#)

Check Contacts

Step 1
Find Friends

Step 2
Profile Information

Step 3
Profile Picture

Are your friends already on Facebook?

Many of your friends may already be here. Searching your email account is the fastest way to find your friends on Facebook.




Gmail

Your Email:

Email Password:

Find Friends

 Facebook will not store your password.



Yahoo!

[Find Friends](#)



Windows Live Hotmail

[Find Friends](#)



Other Email Service

[Find Friends](#)

WHY IS THIS BAD?

**EVEN THOUGH IT
ONLY NEEDS
ACCESS TO
SOME DATA...**

**YOU'VE GIVEN
THE APP ACCESS TO
ALL YOUR DATA**

**NO WAY TO
REVOKE
THE APP'S ACCESS**

YOU PLACE

ALL YOUR TRUST

IN THE APP









Google Contacts

last.fm





Spotify®




buffer



Application







OAuth Server



Facebook wants to access your Google Account

 aaron.parecki@gmail.com

This will allow Facebook to:

-  See and download your contacts 
-  See, edit, download, and permanently delete your contacts 

Make sure you trust Facebook

You may be sharing sensitive info with this site or app. You can always see or remove access in your [Google Account](#).

Learn how Google helps you [share data safely](#).

See Facebook's Privacy Policy and Terms of Service.

[Cancel](#)

[Allow](#)

Authorize Example App to access your account?

Authorize app

Cancel

This application will be able to:

- See Tweets from your timeline (including protected Tweets) as well as your Lists and collections.
- See your Twitter profile information and account settings.
- See accounts you follow, mute, and block.

Learn more about third-party app permissions in the [Help Center](#).



Example App

By Aaron Parecki

example-app.com

Free Version Control with unlimited private and public repositories.



Authorize OAuth 2 Example App



OAuth 2 Example App by [aaronpk](#)
wants to access your **aaronpk** account



Personal user data
Full access



Repositories
Public only



Organization access

 **indieweb** ✓

 **microformats** ✓

 **oauth2** ✓

 **okta** ✓

 **w3c** ✓

Authorize aaronpk

Authorizing will redirect to
<https://example-app.com.dev>



Example App by [Aaron Parecki](#) would like the ability to access the following data in your Fitbit account

- ☒ Select All
- ☒ activity and exercise
- ☒ weight ⓘ
- ☒ sleep
- ☒ food and water logs ⓘ
- ☒ location and GPS
- ☒ profile ⓘ
- ☒ heart rate

Deny



Allow


Data shared with aaronpk will be governed by Aaron Parecki's privacy policy and terms of service. You can revoke this consent at any time in your Fitbit [account settings](#). More information about these permissions can be found [here](#).








Signed in as aaron@parecki.com
[Not you?](#)



**WHAT ABOUT
FIRST-PARTY APPS?**











<https://krausefx.com/blog/ios-privacy-stealpassword-easily-get-the-users-apple-id-password-just-by-asking>

Archive Spam Delete | Mark as unread Snooze | Move to Labels More

"Q1 Bonus" Inbox x



Frank Abagnale <frank.abagnale@noreply-icloud.com>
to aaron ▼

11:20 AM (0 minutes ago)



Reply



Open my shared folder:



Q1 Bonus
iCloud Drive


 Reply

 Reply all

 Forward



Anyone can use Pages, Numbers, and Keynote for iCloud
[Create your free Apple ID and get started today >](#)



Sign in to iCloud

aaron@parecki.com

Password



☐ Keep me signed in

[Forgot Apple ID or password? ↗](#)



Your Apple ID is being used to sign in to a new device.

Enter this verification code on the web to sign in. Don't share it with anyone.



9 6 3 6 4 2

Done

**THEN WHAT GOOD IS
MULTI-FACTOR
AUTHENTICATION?**

Phishable MFA


678328 is your Microsoft Azure verification code





Non-Phishable MFA

WebAuthn




fido™













 **Secure** | <https://apple.com>




 **Secure** | <https://google.com>




Application




OAuth Server



Application




OAuth Server




Application





OAuth Server




REGISTRATION AND ACCOUNT RECOVERY



Application



OAuth Server



A cartoon illustration of a young man with dark hair and glasses, looking surprised or questioning. He is pointing his right index finger towards a login interface. The background shows a window with a grid pattern.

f Sign in with Facebook

g+ Sign in with Google

in Sign in with LinkedIn

t Sign in with Twitter

IS THIS OAUTH?

**OAuth PROVIDES
ACCESS TO DATA**



WHAT IS THIS THEN?

 Sign in with Facebook

 Sign in with Google

 Sign in with LinkedIn

 Sign in with Twitter



+

custom stuff

+





Accessing APIs



Identification



**AVOIDS
HANDLING
PASSWORDS**

**ENABLES
STRONG
MULTI-FACTOR
AUTH**

**OFFLOADS
COMPLEXITY**

GETTING STARTED



oauth.net

specs, extensions and links to resources

oauth.wtf

my video course and book

OAUTH 2.1

[[Search](#)] [[txt](#)|[html](#)|[pdf](#)] [[Tracker](#)] [[WG](#)] [[Email](#)] [[Diff1](#)] [[Diff2](#)] [[Nits](#)]

Versions: ([draft-parecki-oauth-v2-1](#)) [00](#) [01](#) [02](#) [03](#)
[04](#)

OAuth Working Group

Internet-Draft

Intended status: Standards Track

Expires: 8 April 2022

D. Hardt

Hellō

A. Parecki

Okta

T. Lodderstedt

yes.com

5 October 2021

The OAuth 2.1 Authorization Framework draft-ietf-oauth-v2-1-04

Abstract

The OAuth 2.1 authorization framework enables a third-party application to obtain limited access to an HTTP service, either on behalf of a resource owner by orchestrating an approval interaction between the resource owner and an authorization service, or by

THANK YOU!



@AARONPK
AARONPK.COM
OAUTH.WTF